

NEMA SSL 3-2010

High-Power White LED Binning for General Illumination



NEMA SSL 3

**HIGH-POWER WHITE
LED BINNING FOR
GENERAL ILLUMINATION**

NEMA Standards Publication SSL 3-2010

High-Power White LED Binning for General Illumination

Published by:

National Electrical Manufacturers Association

1300 North 17th Street, Suite 1752

Rosslyn, Virginia 22209

www.nema.org

© Copyright 2010 by the National Electrical Manufacturers Association. All rights including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American Copyright Conventions.

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The National Electrical Manufacturers Association (NEMA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

CONTENTS

Foreword	ii
Introduction	1
1 Scope	1
2 Normative References	1
3 Terms and Definitions	1
4 Color Binning.....	2
4.1 Color Binning of White LEDs.....	2
4.2 Bin Labeling of White LEDs	4
5 Luminous Flux and Luminous Intensity Binning	4
6 Color Rendering Binning.....	4
7 Forward Voltage Binning.....	4

Foreword

The NEMA Solid State Lighting Section has prepared this Standards Publication, based on discussions among numerous LED and SSL manufacturers and integrators.

In the preparation of this Standards Publication, input of users and other interested parties has been sought and evaluated. Inquiries, comments, and proposed or recommended revisions should be submitted to the concerned NEMA product Subdivision by contacting:

Vice President, Technical Services
National Electrical Manufacturers Association
1300 North 17th Street, Suite 1752
Rosslyn, Virginia 22209

Introduction

The binning of LEDs is a practice used by LED manufacturers to manage the variation of LED performance in mass production processes. The inefficiencies of binning may create structural vulnerability in the supply chain for the market. To reduce the risk and at the same time protect product yields, LED manufacturers often choose binning schemes in accordance with their specific or unique mass production process. As a result, the LED components or packages produced by the manufacturers maintain structured variations for their performance characteristics.

Because of the uniqueness of the mass production and quality control process used by each LED manufacturer, the LED products supplied to LED system integrators or assemblers (module makers, luminaire makers, etc.) with similar performance characteristics produced by different manufacturers are binned and labeled differently. The binning structures and labeling (marking) used varies from manufacturer to manufacturer.

Binning structure inconsistency, as a result, requires more effort on the part of LED system integrators and assemblers. More unnecessary testing, verifications, qualification, and validations processes have to take place. As a result, overall solid state lighting (SSL) industry productivity may be negatively influenced. With a rapidly growing SSL market, more LED products will be manufactured and more manufacturers will be participating in the market. This makes it necessary and important to establish industry agreed-upon guidelines to ensure product consistency.

1 Scope

This standard applies to LEDs emitting incoherent, visible radiation in Solid State Lighting applications. It specifies bins and bin codes for LEDs for the following characteristics:

- Color

2 Normative References

ANSI_NEMA_ANSI C78.377-2008 *Specifications for the Chromaticity of Solid State Lighting Products*

ANSI/IESNA RP-16 *Nomenclature and Definitions for Illuminating Engineering*

3 Terms and Definitions

3.1 Bin: A restricted range of LED performance characteristics used to delimit a subset of LEDs near a nominal LED performance as identified by chromaticity and photometric performance.

Note—as the result of small but meaningful variations in the manufacturing process of LED wafers and subsequent dies, the electrical and photometric characteristics of LEDs may vary from LED to LED, even when the dies are from the same wafer.

3.2 Binning: The process of sorting and grouping a manufactured distribution of LED packages into smaller groupings.

3.3 Color Bin: The code to indicate the range of chromaticity variation from a grouping of LED package.