



PROCESS
INDUSTRY
PRACTICES

TECHNICAL CORRECTION
May 2024

Pipeline Systems

PIP PLSMV008
Carbon Steel Plug Valve Descriptions

PURPOSE AND USE OF PROCESS INDUSTRY PRACTICES

This Practice has been prepared by harmonizing technical requirements from existing standards of major industrial operators, contractors, and standards development organizations. While this Practice is intended to incorporate the majority of requirements, individual applications may have requirements which take precedence over this Practice. Determinations concerning fitness for purpose or application of this Practice to specific project or engineering situations should not be made solely on information contained in this Practice. All Practices are intended to be consistent with applicable laws and regulations. Should this Practice conflict with applicable laws or regulations, such laws or regulations must be followed. Consult an appropriate professional before applying or acting on any material contained in or suggested by this Practice.

Use of trade names should not be viewed as an expression of preference. Other brands having the same specifications are equally correct and may be substituted for those named.

This Practice is subject to revision at any time. For more information refer to PIP ADG001, *Specification for Developing Practices*.

© 2017 Process Industry Practices (PIP), Construction Industry Institute, and The University of Texas at Austin on behalf of the Board of Regents of the University of Texas System

Process Industry Practices
3925 West Braker Lane (R4500)
Austin, Texas 78759

PUBLISHING HISTORY

October 2017	Issued	August 2023	Complete Revision
January 2019	Technical Correction	May 2024	Technical Correction

Not printed with State funds



PIP PLSMV008 Carbon Steel Plug Valve Descriptions

Table of Contents

1. Scope	2	5. Cross Reference	3
2. References	2	6. Valve Descriptions.....	4
2.1 Process Industry Practices	2		
3. Valve Designation System	2		
4. Notes	2		

1. Scope

This Practice provides requirements for suppliers providing carbon steel plug valves included in PIP Pipeline Systems Material Specifications (PMSs).

2. References

Applicable parts of the following Practice shall be considered an integral part of this Practice. The edition in effect on the date of contract award shall be used, except as otherwise noted. Short titles will be used herein where appropriate.

2.1 Process Industry Practices (PIP)

- *PIP PLCM0004 - Pipeline Systems Valve Tag Number Designator System*

3. Valve Designation System

- 3.1 For a full explanation of the format used to structure the valve numbers listed within this Practice, refer to PIP PLCM0004.
- 3.2 This Practice provides descriptions for two types of plug valves. Therefore, the first two characters following the Pipeline Systems identifier, L, in the valve numbers are PE or PL.
- 3.3 The valves listed in Section 5 and Section 6 of this Practice are sorted by the unique valve number designation in ascending alphanumeric sequence (e.g., LPE01CB500, LPE01CB501, LPE03CB500, LPL01CB500, LPL01CB501, LPL03CB500, LPL03CB501).

4. Notes

- 4.1 Occasionally, valve size ranges listed in this Practice are broader than the size ranges shown for the same valves on a given PMS. While the “most common practice” has been used to specify valve size ranges on line class specifications, a purchaser may need to utilize a valve in a size outside this “common practice” choice. Thus, for reference purposes, the full size range for which a given valve is typically manufactured is shown in this Practice.
- 4.2 Gear operation may be specified in two ways: (a) Select the description in which the gear operator is already called out, or (b) Select the description in which a handwheel has been called out, and use Field 5 of the Valve Tag Number Designator System as described in PIP PLCM0004.
- 4.3 If fluids can be trapped (e.g., in double-seated valves) and subject to heating and subsequent expansion, means of pressure relief shall be considered to avoid excessive pressure build-up.
- 4.4 Because of current practice at many pipeline facilities, only NACE-compliant valves are specified. These valves are technically acceptable for both sweet and sour services. For use of non-NACE-compliant valves or for applications involving severe sour and corrosive services, engineering review is required.