

NA+A1:2020 to BS EN 1991-2:2003

Incorporating Corrigendum No. 1



BSI Standards Publication

**UK National Annex to Eurocode 1:
Actions on structures —**

Part 2: Traffic loads on bridges

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2020

Published by BSI Standards Limited 2020

ISBN 978 0 580 04401 0

ICS 91.010.30; 93.040

The following BSI references relate to the work on this document:

Committee reference B/525

Draft for comment 06/30128340 DC; 19/30393710 DC

Publication history

First published May 2008

Amendments issued since publication

Amd. no.	Date	Text affected
Cor 1	May 2008	“Timber” removed from title
Amd 1	June 2020	Indicated by tags A1 A1

Contents

	Introduction	1
NA.1	Scope	1
NA.2	Nationally determined parameters	2
	<i>Table NA.1 – Adjustment factors α_Q and α_q for Load Model 1</i>	3
	<i>Figure NA.1 – Basic longitudinal configuration of SV model vehicles</i>	4
	<i>Figure NA.2 – Basic longitudinal configuration of SOV model vehicles</i>	6
	<i>Figure NA.3 – Lateral wheel arrangement for trailer axles of all SOV models</i>	7
	<i>Table NA.2 – Dynamic Amplification Factors for the SV and SOV vehicles</i>	7
	<i>Figure NA.4 – Typical application of SV or SOV and Load Model 1 loading when the SV or SOV vehicle lies fully within a notional lane</i>	8
	<i>Figure NA.5 – Typical application of SV or SOV and Load Model 1 loading when the SV or SOV vehicle straddles two adjacent lanes</i>	9
	<i>Table NA.3 – Assessment of groups of traffic loads (characteristic values of the multi-component action)</i>	11
	<i>Table NA.4 – Indicative numbers of heavy goods vehicles expected per year and per lane in the United Kingdom</i>	12
	<i>Table NA.5 – Set of equivalent lorries for Fatigue Load Model 4</i>	14
	<i>Table NA.6 – Forces due to collision with vehicle restraint systems for determining global effects</i>	15
	<i>Figure NA.6 – Vehicle model for abutments and wing walls</i>	16
	<i>Table NA.7 – Recommended crowd densities for design</i>	19
	<i>Figure NA.7 – Effective span calculation</i>	20
	<i>Table NA.8 – Parameters to be used in the calculation of pedestrian response</i>	20
	<i>Figure NA.8 – Relationships between $k(f_v)$ and mode frequencies f_v</i>	21
	<i>Figure NA.9 – Reduction factor, γ, to allow for the unsynchronized combination of pedestrian actions within groups and crowds</i>	22
	<i>Table NA.9 – Recommended values for the site usage factor k_1</i>	24
	<i>Table NA.10 – Recommended values for the route redundancy factor k_2</i>	24
	<i>Table NA.11 – Recommended values for the structure height factor k_3</i>	24
	<i>Figure NA.10 – Response modifiers</i>	24
	<i>Figure NA.11 – Lateral lock-in stability boundaries</i>	26
	<i>Table NA.12 – Nominal longitudinal loads</i>	27
	<i>Figure NA.12 – RL Loading</i>	28
	<i>Table NA.13 – Nominal longitudinal loads (RL loading)</i>	30
	<i>Table NA.14 – Standard load spectra for RL loading</i>	31
	<i>Table NA.15 – RL loading: Annual traffic tonnage and composition of standard traffic mix</i>	31
	<i>Figure NA.13 – Trains included in Table NA.14 spectra</i>	32
	<i>Figure NA.14 – Flow chart for determining whether a dynamic analysis is necessary for “simple” structures</i>	34
	<i>Figure NA.15 – Flow chart for determining whether a dynamic analysis is required for “simple” and “complex” structures</i>	35
	<i>Figure NA.16 – Limits of bridge natural frequency n_0 in Hz as a function of L in m</i>	36
	<i>Figure NA.17 – Coordinate system</i>	40
	<i>Figure NA.18 – Pressure distributions on a vertical structure next to the track</i>	41
	<i>Figure NA.19 – Pressure distributions on a horizontal structure above the track</i>	42

	<i>Figure NA.20 – Pressure loads on a horizontal structure adjacent to the track</i>	44
	<i>Figure NA.21 – Pressure distributions on a multi-surface structure next to the track</i>	45
NA.3	Decision on the status of informative annexes	47
NA.4	References to non-contradictory complementary information	48
	Bibliography	49

Summary of pages

This document comprises a front cover, an inside front cover, pages i to ii, pages 1 to 49, and a back cover

National Annex (informative) to BS EN 1991-2:2003, Eurocode 1: Actions on structures – Part 2: Traffic loads on bridges

Introduction

This document has been prepared by BSI Subcommittees B/525/1, *Actions (loadings) and basis of design*, and B/525/10, *Bridges*. In the UK it is to be used in conjunction with BS EN 1991-2:2003.

NA.1 Scope

This document gives:

- a) the UK decisions for the Nationally Determined Parameters described in the following subclauses of BS EN 1991-2:2003:

- | | |
|--|-------------------------------------|
| — 1.1 (3) | — 6.5.4.1 (5) |
| — 2.2 (2) Note 2 | — 6.5.4.3 (2) Notes 1 and 2 |
| — 2.3 (1) Note and (4) Note | — 6.5.4.4 (2) Note 1 |
| — 3 (5) | — 6.5.4.5 |
| — 4.1 (1) Note 2 and (2) Note 1 | — 6.5.4.5.1 (2) |
| — 4.2.1 (1) Note 2 and (2) | — 4.7.3.3 (1) Notes 1 and 3 and (2) |
| — 4.2.3 (1) | — 4.7.3.4 (1) |
| — 4.3.1 (2)(b) Note 2 | — 4.8 (1) Note 2 and (3) |
| — 4.3.2 (3) Notes 1 and 2 and (6) | — 4.9.1 (1) Note 1 |
| — 4.3.3 (2) and (4) | — 5.2.3 (2) |
| — 4.3.4 (1) | — 5.3.2.1 (1) |
| — 4.4.1 (2), (3) and (6) | — 5.3.2.2 (1) |
| — 4.4.2 (4) | — 5.3.2.3 (1) Note 1 |
| — 4.5.1 (Table 4.4a Notes a and b) | — 5.4 (2) |
| — 4.5.2 (1) Note 3 | — 5.6.1 (1) |
| — 4.6.1 (2) Note 2c), (3) Note 1 and (6) | — 5.6.2.1 (1) |
| — 4.6.4 (3) | — 5.6.2.2 (1) |
| — 4.6.5 (1) Note 2 | — 5.6.3 (2) Note 2 |
| — 4.6.6 (1) | — 5.7 (3) |
| — 4.7.2.1 (1) | — 6.1 (2), (3)P and (7) |
| — 4.7.2.2 (1) Note 1 | — 6.3.2 (3)P |
| — 6.4.6.1.1 (6) Table 6.4 and (7) | — 6.3.3 (4)P |
| — 6.4.6.1.2 (3) Table 6.5 | — 6.4.4 (1) |
| — 6.4.6.3.1 (3) Table 6.6 | — 6.4.5.2 (3)P |
| — 6.4.6.3.2 (3) | — 6.4.5.3 (1) Table 6.2 |
| — 6.4.6.3.3 (3) Notes 1 and 2 | — 6.5.4.6 |
| — 6.4.6.4 (4) and (5) | — 6.5.4.6.1 (1) and (4) |
| — 6.5.1 (2) | — 6.6.1 (3) |
| — 6.5.3 (5) and (9) | — 6.7.1 (2)P and (8) |